

**CONTINENTAL™**  
BUILDING PRODUCTS



### Applications

Bison Board Rapid Deco Abuse Type X drywall is the best solution for interior areas specified for a Level 5 finish and where a higher resistance to abrasion, indentation and impact penetration is required. Applicable areas include:

- High-end residential and commercial construction
- Hotel lobbies and other high-traffic, public spaces
- Areas with considerable natural light exposure and where critical lighting or gloss paints are specified

### Advantages

- Provides an equivalent to a field-applied Level 5 finish in the same number of steps as a Level 4 finish
- Abuse resistant per ASTM C1629
- Fire resistance with very low flame spread
- Low installation cost
- Creates a uniform surface and the highest-quality finish
- Provides consistent job results
- Minimizes jobsite application labor and reduces cost over a field-applied Level 5 finish
- Installs in the same manner as traditional drywall — no special tools or enhanced skills required
- Superior Level 5 results in less time

## FIRE- AND ABUSE-RESISTANT LEVEL 5 FACTORY-FINISHED DRYWALL

# BISON BOARD™ RAPID DECO® ABUSE TYPE X

**Continental Building Products** Bison Board Rapid Deco Abuse Type X drywall is a fire- and abuse-resistant gypsum board pre-finished with a specially formulated material to facilitate finishing to a Level 5 finish. This material is factory-applied to provide a consistent and uniform finish. Rapid Deco Abuse Type X is installed in the same manner as traditional drywall and finished with Rapid Deco joint compound to easily and quickly produce a Level 5 finish (Please refer to the Rapid Deco joint compound submittal sheet for technical information).

Rapid Deco Abuse Type X is designed for use in applications that require direct mechanical attachment to wood or metal framing, or as a component of fire-rated assemblies. May also be used as a thermal barrier in roof assemblies when specified by the roofing manufacturer. To ensure optimum Type X fire resistance performance, follow recommended installation procedures for fire-rated assemblies. When properly sealed and used in a certified sound-rated assembly, Rapid Deco Abuse Type X will also contribute to the required sound transmission classification (STC) values.

Note: Rapid Deco Abuse Type X is suitable for interior applications only and should not be used where temperatures exceed 125 °F for extended periods or in areas of extreme humidity. Likewise, the board should be protected from exposure to adverse conditions during storage and construction.

**Rapid Deco System:** Consists of a factory-finished Level 5 drywall and a specially formulated, matching joint compound. Used together, they create an equivalent substitution to a field-applied Level 5 finish (per ASTM C840).

### Test Results per ASTM C1629

JOB NAME: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_

DATE: \_\_\_\_\_

Soft Body Impact	210 ft. lbs.	Level 2
Surface Abrasion	< 0.010"	Level 3
Surface Indentation	0.133"	Level 1
Hard Body Impact	70 ft. lbs.	Level 1

## Sustainability


Can contribute to the U.S. Green Building Council's LEED Credit Qualification in several credit categories to assist in obtaining LEED certification.



**Limitations:** Rapid Deco is designed to replicate a field-applied skim coat. A skim coat will not approximate a plastered surface. For an entirely smooth, blemish-free surface, a veneer plaster or hard-wall plaster system is recommended. See Gypsum Association publication GA-214 for additional details on skim coating.

Continental cannot control the workmanship of the installed or finished product. Finish satisfaction will only be obtained when proper installation practices are followed and products are properly used. Care must be taken to ensure all joints, trim and fasteners are properly treated and are flat to the plane of the board surface.

Continental cannot control the painting and decorating process. Architectural specifications for decoration and manufacturer's product application instructions must be strictly followed to obtain finish satisfaction.



**CONTINENTAL™**

### CONTINENTAL BUILDING PRODUCTS

USA (800) 237-5505  
Canada (866) 649-7786  
www.continental-bp.com

## Physical Characteristics

**Core:** Non-combustible, dimensionally stable, inert gypsum enhanced with glass fiber for strength and fire resistant

**Paper:** 100% recycled; Face paper coated with a specially formulated skim-coat material; Edges = ivory, back = gray

**Long Edges:** Tapered

**Asbestos free and GREENGUARD certified**

## Standards and Codes

Formulated to perform in accordance with ASTM C1396/C1396M, Section 5, Gypsum Wallboard, Type X (factory-finished per ASTM C840 Level 5); Abuse Resistant per ASTM C1629M; and CAN/CSA-A82.27-M.

## Technical Specifications

UL classified for surface burning (File No. R16102) (per ASTM E84 and CAN/ULC-S102) Flame spread = 0; Smoke developed = 0; Meeting IBC, Section 803.1, Class A

Core combustibility (per ASTM E 136) Non-combustible

UL classified for fire resistance (File No. R18482) as Type LGFC6A per ASTM E119 and CAN/ULC-S101

## Installation

When installed on steel studs, standard 20 gauge (for use of 20 gauge EQ studs, contact stud manufacturer) or heavier studs should be used. Install according to Gypsum Association GA-216 or ASTM C840. For fire-rated construction, consult GA-600 Fire Resistance Design Manual and UL Fire Resistance Directory. Rapid Deco joint compound should be used for best match to Rapid Deco drywall. Refer to GA-214 for more finishing recommendations.

## Painting and Decorating

A jobsite mock-up shall be used to determine the level of workmanship needed at each stage of finishing. It is recommended that a visual inspection be done prior to painting to confirm that proper finishing practices have been followed to avoid anomalies in the painting and decorating process. A flat drywall primer with a minimum volume solids content of 34% is recommended. Under no circumstances should an all-in-one paint and primer or a sealer-type primer be used.

## Handling Recommendations

Stack flat, keep dry and lift (do not drag) to avoid scuffing. Avoid damage to edges. For detailed recommendations, refer to GA-216 and GA-801.

## Safety Precautions

Wear safety glasses and NIOSH-approved respirators during cutting, breaking, rasping or other dust-producing activities.

Safety Data Sheets (SDS) are available for all Continental products upon request.

## Available Sizes:

Nominal thickness	5/8 in.
Nominal width	4 ft..
Standard length	10 ft. and 12 ft. (other lengths available by special order)
Nominal weight	2.8 lbs./ft. <sup>2</sup>

